



UNIMIG 418



ENG • Three-phase industrial MIG welding units on wheels, equipped with 4 rolls separate wire feeder. They are all equipped with 5m interconnecting cable, euro connection torch, Gas regulator, gas hose, ground cable and clamp. They are equipped with timer for spot welding and with welding current and arc voltage displays. These professional units are fitted with manual (2T) and automatic (4T) welding selector, slope up ramp and burn back time adjustment feature. Well suited for medium sized industrial welding workshop. The reel holder will accept spools from 5 to 15 Kg.

IT • Saldatrici industriali a filo continuo trifase carrellate, corredate di trainafile separato 4 rulli. Le saldatrici sono corredate di fascio cavi 5m, torcia - attacco euro, riduttore di pressione, tubo gas, pinza e cavo di massa. Sono dotate di timer per la saldatura a punti e di display per la visualizzazione della corrente di saldatura e della tensione d'arco. Dotate di selettore per saldatura manuale (2T) e automatica (4T), regolatore della rampa di partenza e del tempo di post bruciatura. Impianti particolarmente adatti nelle medie carpenterie ed industrie. Il porta bobine consente di utilizzare bobine da 5 a 15 Kg.

UNIMIG 418	
	(3ph) 230/400V 50/60Hz
Power 60%	19 KVA
U ₀	17 ÷ 43 V
Amp. Min-Max	30 ÷ 400 A
Amp. 60974-1	60% 400 A 100% 310 A
Adjust. Pos.	24
Steel	Ø 0,6 ÷ 1,6 mm
Stainless Steel	Ø 0,8 ÷ 1,2 mm
Aluminium	Ø 0,8 ÷ 1,6 mm
Insulation	H
Protec. degree	IP23S
(LxWxH)	1000x555x1340 mm
(LxWxH)	Gen 1070x475x870 mm W.F. 685x290x485 mm
box/net	192 / 174,6 Kg
Code	99425050K

ACCESSORIES INCLUDED

Generator 99415043

Wire Feeder T4 99420048

Interconnection cable • 70 mm² • 5,0 meters

MIG torch TBI 360 • 4,0 meters

Ground cable • 50 mm² • 3,0 meters

Gas regulator CO₂ Maxi • 2 gauges

Adaptor for gas bottle CO₂ - Ar

EXTRA ACCESSORIES

21905073 Adjustable face shield • 2 sensors

21905086 HD welding gloves for MIG/MMA welding