



VACUUM CLEANERS - DUST EXTRACTORS - HEAVY TOOLINGS

GS 3/78 OPT CYC

POWER MAX

3500
W

WATER LIFT

2230
mmH₂O

AIRFLOW

765
m³/h

TANK CAPACITY

78
l

EXCLUSIVE FEATURES

- ▶ INNOVATIVE GASKET
- ▶ STRONG HOOKS
- ▶ INDEPENDENT MOTORS WITH LIGHT SWITCHES
- ▶ TIPPING TROLLEY
- ▶ MICROFIBER BAG
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ DETACHABLE TANK AND SOLID CART
- ▶ MULTI STAGE FILTRATION
- ▶ BIG AND BRAKED WHEELS
- ▶ ELECTROSTATIC DISSIPATION



MOST FREQUENTLY USE

AGRICULTURE



CONSTRUCTION



HARDWARE CUSTOMER



HEAVY INDUSTRY



INNOVATIONS



SPECS



OPTIM TROLLEY IS EXTREMELY DURABLE AND MANEUVERABLE



CYCLONE SYSTEM



TIPPING TANK

TECHNICAL DATA

		GS 3/78 OPT CYC
Code		ASD015517
PERFORMANCE		
Usage		DRY
Motor		3
Power	W	3400-3500 max
Voltage	V	220-240
Water lift	mmH ₂ O	2230
Airflow	m ³ /h	765
Tank Capacity/Material	l	78/steel
Cable length	m	8,5
Filtering surface	cm ²	2260
Sound Pressure Level (EN 60704-1; EN 60704-2-1; IEC 60335-2-69)	dB(A)	76
Diameter of accessories	mm	50
Dimensions (LxWxH)	mm	600x620x1335
Weight	kg	43

STANDARD EQUIPMENT

CODE: MPVR28723
FASTENING PLASTIC RING



CODE: FTDP28843
HEPA H13 CARTRIDGE
2.260 cm²



CODE: -
MICROFIBER BAG 12 l



CODE: TBFX01270
CONDUCTIVE FLEXIBLE HOSE 5 m Ø50 mm



OPTIONAL ACCESSORIES

CODE: KTRI04795
MICROFIBER BAG SET OF 10 PCS



X10

CODE: SPPV49597
RUBBER FLAT LANCE
Ø50 mm



CODE: LAFN49581
COMPLETE ALUMINIUM DOUBLE WAND
Ø50 mm



CODE: SPPV01960
BRISTLE BRUSH Ø50 mm



CODE: KTRI05290
CONDUCTIVE KIT 2 OPERATORS
Ø38/60 mm



CODE: TBFX00933
CONDUCTIVE FLEXIBLE HOSE 10 m Ø50 mm

